

MAKE A LASTING IMPACT

The new Impact™ On-Wall Kiosk brings a new flexibility to the digital signage enclosure market while maintaining a sleek aesthetic to complement a variety of environments. A depth-adjustable exterior frame allows for a variety of displays to be used and accommodates future display changeouts. An exclusive swing frame design keeps the display mounted to the frame when opened for unparalleled service and maintenance access.



- Depth-adjustable exterior frame can be set between 3-5" (76 - 127 mm) to accommodate a wide variety of flat panel depths
- Display stays mounted to swing frame when opened to provide full access to components and cabling
- Reversible hinges help to avoid installation and service obstructions
- Designed with hidden, passive cooling vents – active thermal management and power upgrade sold separately
- Integrated wall reveal compensates for uneven walls, keeping the front of the frame flat
- Tamperproof security hardware protects technology investments
- To avoid cutting into walls, tool-free on-wall storage is included utilizing Middle Atlantic's Lever Lock™ technology; additional on-wall storage available with purchase of PACUNV accessory
- Large center opening allows for additional storage utilizing Chief's In-wall Storage Boxes: PAC525, PAC526 and PAC527
- Standard black and white finish options



DEPTH
ADJUSTMENT



KIOSK LATCH



LEVER LOCK™




VENTILATION
LOUVERS

ACCESSORIES



PAC525, PAC526 & PAC527
In-Wall Storage Boxes



PACUNV Series
Lever Lock™
Tray Options



PACFAN Series
Active Thermal Management
Fan Kit Options

DIMENSIONS & COMPATIBILITY

Model	Color	Weight Capacity	Mounting Patterns	Max TV Width	Max TV Height	Image Diagonal (A)	Overall Width (B)	Overall Height (C)	Viewing Area Width (D)	Viewing Area Height (E)	Side Bezels (F)	Top/Bottom Bezels (G)		
LW46UBP	Black	100 lbs (45.3 kg)	300 x 300 mm 400 x 400 mm	43" (1092.2 mm)	26" (660.4 mm)	46"	28.5" (723.9 mm)	46.5" (1181.1 mm)	22.5" (571.5mm)	40.1" (1018.5 mm)	3" (76.2 mm)	3.2" (81.3 mm)		
LW46UWP	White					47"			23" (584.2 mm)	40.9" (1038.9 mm)	2.75" (69.9 mm)	2.8" (71.1 mm)		
LW47UBP	Black					48"			23.5" (596.9 mm)	41.5" (1054.1 mm)	2.5" (63.5 mm)	2.5" (63.5 mm)		
LW47UWP	White					49"			23.8" (604.5 mm)	42.3" (1074.4 mm)	4.35" (109.2 mm)	6.1" (154.9 mm)		
LW48UBP	Black					50"			24.3" (617.2mm)	43.1" (1094.74)	4.1" (104.1 mm)	5.7" (144.8 mm)		
LW48UWP	White					55"			26.8" (680.7 mm)	47.6" (1209 mm)	2.85" (72.4 mm)	3.45" (87.6 mm)		
LW49UBP	Black	125 lbs (56.7 kg)	300 x 300 mm 400 x 400 mm	51" (1295.4 mm)	30" (762.0 mm)	49"	32.5" (825.5 mm)	54.5" (1384.3 mm)	23.8" (604.5 mm)	42.3" (1074.4 mm)	4.35" (109.2 mm)	6.1" (154.9 mm)		
LW49UWP	White					50"			24.3" (617.2mm)	43.1" (1094.74)	4.1" (104.1 mm)	5.7" (144.8 mm)		
LW50UBP	Black					55"			26.8" (680.7 mm)	47.6" (1209 mm)	2.85" (72.4 mm)	3.45" (87.6 mm)		
LW50UWP	White					65"			31.6" (802.6 mm)	56.2" (1427.5 mm)	3.7" (94 mm)	5.15" (129.5 mm)		
LW55UBP	Black					70"			34.1" (866.1 mm)	60.6" (1539.2 mm)	2.45" (61 mm)	2.95" (74.9 mm)		
LW55UWP	White					75"			36.5" (927.1 mm)	66.5" (1689.1 mm)	2.5" (63.5 m)	3.25" (82.6 mm)		
LW65UBP	Black	175 lbs* (79.4 kg)	300 x 300 mm 400 x 400 mm 600 x 400 mm 600 x 600 mm	63" (1600.2 mm)	36.5" (927.1 mm)	65"	39" (990.6 mm)	66.5" (1689.1 mm)	31.6" (802.6 mm)	56.2" (1427.5 mm)	3.7" (94 mm)	5.15" (129.5 mm)		
LW65UWP	White					70"			34.1" (866.1 mm)	60.6" (1539.2 mm)	2.45" (61 mm)	2.95" (74.9 mm)		
LW70UBP	Black					75"			36.5" (927.1 mm)	66.5" (1689.1 mm)	2.5" (63.5 m)	3.25" (82.6 mm)		
LW70UWP	White					68" (1727.2 mm)			39" (990.6 mm)	71.5" (1816.1 mm)	36.5" (927.1 mm)	65" (1651 mm)	2.5" (63.5 m)	3.25" (82.6 mm)
LW75UBP	Black					75"			41.5" (1054.1 mm)	71.5" (1816.1 mm)	36.5" (927.1 mm)	65" (1651 mm)	2.5" (63.5 m)	3.25" (82.6 mm)
LW75UWP	White					75"			41.5" (1054.1 mm)	71.5" (1816.1 mm)	36.5" (927.1 mm)	65" (1651 mm)	2.5" (63.5 m)	3.25" (82.6 mm)

* 175lbs for wood stud, plywood backed steel stud, block & concrete. 125lbs in steel stud.

SPECIFICATIONS

Orientation: Portrait

Exterior Frame Depth Range: 3-5" (76 - 127 mm)

Max Display Depth: 3.75" (95 mm)

NOTE: To keep the exterior frame depth at 4" (102 mm) or less a maximum display depth of 2.75" (69 mm) can be used.

On-Wall Storage Width (H): 16.5" (419 mm)

On-Wall Storage Height (I): 6.4" (163 mm) for 46-48" models; 10.4" (264 mm) for 49-75" models

On-Wall Storage Depth (J): Dependent on depth of display and desired frame depth; see Side of Frame view and below equations for details

- **Overall Kiosk Depth:** $L = 1.25" + K$
- **On-Wall Storage Depth:** $J = L - K - 3/4"$

