MAXHUB

Commercial Display

Model Name: ND98CMA

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more effective and productive.









Professional 4K Display

4K Resolution Anti-Glare, 25% Haze

Wireless Screen Sharing

Share your screen through MAXHUB Share app or wireless dongle

External Control

Display Control through IP or RS232 protocol

Device Management

Manage through cloud based MAXHUB Pivot



Built-in Speakers

2 × 10W Dual speakers

Upgrade Your Display

OPS slot availability to transform your display into a windows-based display



Conformal Coating

Commercial level design of hareware



Energy Saving

ErP Certified Energy Star 8.0 Certified

Commercial Display

Screen Size (class)	98"
Diagonal	97.5" / 247.7cm
Panel Type	ADS
Haze	25% (Anti-Glare)
Aspect Ratio	16:9
Native Resolution	3840 × 2160
Refresh Rate	60Hz
Brightness (Typ.)	500 nits
Backlight Type	DLED
Contrast Ratio	1,200:1 (Typ) 1,000,000:1 (Dynamic)
Viewing Angle (H × V)	178°
Response Time	8ms
Life Time (Min.)	≥50,000 hours
Operation Hours (Hours / Day)	24/7
Orientation Internal Player	Portrait / Landscape
Processor	A55 × 4
Graphic	Mali-G52 × 2
Memory	4G
Chave as	32G
Storage	Android 11.0
Storage Operating System	

Environmental Conditions

Operation Temperature	0°C ~ 40°C
Operation Humidity	10% ~ 90%RH
Storage Temperature	-20°C ~ 60°C
Storage Humidity	10% ~ 90%RH
Power	
Power Supply	100-240V~50/60Hz
Power Supply Power Consumption (Typical)	100-240V~50/60Hz 340W

1700					
178°	Sound				
8ms	Speaker Dow	or Output		$2 \times 10 M$	
≥50,000 hours	Speaker Powe	erOutput		$\angle \times 1000$	
24/7					
Portrait / Landscape	Certificati	on			
	Safety			IEC 62368-1	
	EMC			Class B	
A55 × 4	ErP			Yes	
Mali-G52 × 2	Energy Star			Yes	
4G					
32G	Features				
Android 11.0	Built-In Media	a Player		Yes	
4K		-			
HDMI IN 2.0 × 3	Accessory	/			
USB Type-C × 1 (PD 65W) USB Type-A 3.0 × 1 (for external peripherals) USB Type-A 2.0 × 1 (only for firmware upgrade) RJ45 IN × 1 HDMI OUT 2.0 × 1	Included in th	ne package		Power Cord × 1 HDMI Cable × 1 Wi-Fi Module × 1 Remote Control × 1	
SPDIF × 1 (Optical)					
RJ45 OUT × 1 AUDIO OUT × 1 (3.5mini jack)	Optional				
RS232 × 1 / IR Receiver		OPS (OPS62A)	Wireless Dongle (WT13)	Mobile Stand (ST41B)	Mobile Stand (ST23C)
Removable Wi-Fi Module					
Wi-Fi 6 Support	Warranty				
2.4GHz & 5GHz					
802.11ac/b/g/n/a/ax	Display			3 years warranty	
	> 50,000 hours 24 / 7 Portrait / Landscape JAG Ali-G52 × 2 Adi 32G Android 11.0 K JDMI IN 2.0 × 3 JSB Type-C × 1 (PD 65W) JSB Type-A 3.0 × 1 (for external peripherals) JSB Type-A 3.0 × 1 (for external peripherals) SyB Type-A 3.0 × 1 (for external peripherals) <td< td=""><td>Speaker Power 24 / 7 Portrait / Landscape Safety Safety Safety EMC EMC EMC EMC EMC EMC EMC EMC</td><td>>50,000 hoursSpeaker Power Output24 / 7CertificationPortrait / LandscapeCertificationAfs × 4EMCAll-G52 × 2Energy Star4GFP32GAndroid 11.0AKBuilt-In Media Player4KDevice Management SystemVIDENTY PLANANT (IP DESTRY) VISB Type-A 3.0 × 1 (for external peripherals) Systep - X 100 yfor firmware upgrades R45 N × 1AccessoryHDMI IN 2.0 × 3 VISB Type-A 3.0 × 1 (for external peripherals) Systep - X 100 yfor firmware upgrades R45 N × 1AccessoryHDMI OUT 2.0 × 1 Systep - X 100 yfor firmware upgrades R45 N × 1Optional Optional Optional OPS (OPS62A)RE323 × 1 / IR Receiver Wi-Fi 6 SupportFurther Start Systep - X 100 yfor firmware upgrades OPS (OPS62A)</td><td>sequence server Output Speaker Power Po</td><td>\$Polymer Output \$pageker Power Output 2 × 10W 24 / 7 Portrait / Landscape Certification EC 62368-1 Portrait / Landscape Safety IE 62368-1 IE 62368-1 Afsonome FiP Vers IE 62368-1 Ail-G52 × 2 Ferb Vers Vers Add Fortures Vers Vers Addright 11.0 Built-In Media Player Vers Vers Addright 12.0 Built-In Media Player Vers Vers Vers Screen Share MAXHUB Photo Vers Systep A 3.0 × 1 (for external peripherals) Vers Vers NaxHUB Share VBMI IN 2.0 × 3 Nathub Proton Vers Nathub Proton Systep A 3.0 × 1 (for external peripherals) Vers Vers Nathub Photon × 1 VBMI IN 2.0 × 3 Vers Vers Nathub Photon × 1 Systep A 3.0 × 1 (for external peripherals) Vers Vers Nathub Photon × 1 VBMI IN 2.0 × 3 Vers Vers Vers Nathub Photon × 1 VBMI IN 2.0 × 3 Vers Vers Vers Nathub Photon × 1 </td></td<>	Speaker Power 24 / 7 Portrait / Landscape Safety Safety Safety EMC EMC EMC EMC EMC EMC EMC EMC	>50,000 hoursSpeaker Power Output24 / 7CertificationPortrait / LandscapeCertificationAfs × 4EMCAll-G52 × 2Energy Star4GFP32GAndroid 11.0AKBuilt-In Media Player4KDevice Management SystemVIDENTY PLANANT (IP DESTRY) VISB Type-A 3.0 × 1 (for external peripherals) Systep - X 100 yfor firmware upgrades R45 N × 1AccessoryHDMI IN 2.0 × 3 VISB Type-A 3.0 × 1 (for external peripherals) Systep - X 100 yfor firmware upgrades R45 N × 1AccessoryHDMI OUT 2.0 × 1 Systep - X 100 yfor firmware upgrades R45 N × 1Optional Optional Optional OPS (OPS62A)RE323 × 1 / IR Receiver Wi-Fi 6 SupportFurther Start Systep - X 100 yfor firmware upgrades OPS (OPS62A)	sequence server Output Speaker Power Po	\$Polymer Output \$pageker Power Output 2 × 10W 24 / 7 Portrait / Landscape Certification EC 62368-1 Portrait / Landscape Safety IE 62368-1 IE 62368-1 Afsonome FiP Vers IE 62368-1 Ail-G52 × 2 Ferb Vers Vers Add Fortures Vers Vers Addright 11.0 Built-In Media Player Vers Vers Addright 12.0 Built-In Media Player Vers Vers Vers Screen Share MAXHUB Photo Vers Systep A 3.0 × 1 (for external peripherals) Vers Vers NaxHUB Share VBMI IN 2.0 × 3 Nathub Proton Vers Nathub Proton Systep A 3.0 × 1 (for external peripherals) Vers Vers Nathub Photon × 1 VBMI IN 2.0 × 3 Vers Vers Nathub Photon × 1 Systep A 3.0 × 1 (for external peripherals) Vers Vers Nathub Photon × 1 VBMI IN 2.0 × 3 Vers Vers Vers Nathub Photon × 1 VBMI IN 2.0 × 3 Vers Vers Vers Nathub Photon × 1

Mechanical Specification

Bezel Width (L × R × T × B)

26 / 26 / 26 / 26 mm

102/102/102/102

	1.027	1.027	1.027	1.02 Inch	
--	-------	-------	-------	-----------	--

Product Dimension (W × H × D)	2212.9 × 1268.4 × 79.4 mm 87.12 × 49.94 × 3.13 inch
Package Dimension (W × H × D)	2360 × 1425 × 280 mm 92.91 × 56.10 × 11.02 inch
Product Weight (Net)	69.90 kg / 154.10 pounds
Package Weight (Gross)	90.8 kg / 200.2 pounds
VESA Mount (mm)	800 × 600









https://www.facebook.com/MAXHUB.Global

in https://www.linkedin.com/company/maxhub-overseas/