











MAXHUB UC S15

Ultra-Wide Angle, All-in-One Collaboration Videobar for Huddle & Small Rooms

The MAXHUB UC S15 is a 4K wide-angle BYOD Videobar with an outstanding acoustic solution, as well as a meeting platform for huddle and small meeting rooms. With a simple interface, a single-click launcher, and a plethora of collaborative tools, it's a breeze to get started. In addition, UC S15's BYOM integration with WT13M makes it simple to share content, as well as the device's built-in camera, microphone, and speakers.



- | | | | |
|--|---|---|--|
|  <p>Ultra HD 4K
Exceptional UHD video quality</p> |  <p>120° FOV
Provides full-room coverage</p> |  <p>Auto Framing
AI Vision
Intelligent face detection</p> |  <p>BYOM
Wireless content and camera, microphone, and speaker sharing</p> |
|  <p>Voice Localization
Speaker tracking
Voice tracking</p> |  <p>PoE
PoE support that simplifies installation and minimizes cost</p> |  <p>Built-in System
Agnostic meeting platform</p> |  <p>PIR Sensor
Auto on/off
Completely hands-free and energy saving</p> |

Camera

Pixel	12 M		
Sensor	1/2.3-inch 12 MP Sony sensor		
ZOOM	5x Digital Zoom		
Resolution and Frame Rate:			
MJPEG/H264:	(1) 3840 x 2160	(2) 2560 x 1440	(3) 1920 x 1080
	(4) 1280 x 720	(5) 1024 x 576	(6) 960 x 540
	(7) 800 x 600	(8) 640 x 480	(9) 640 x 360
	(10) 480 x 270	(11) 352 x 288	(12) 320 x 240
	(13) 320 x 180		
NV12/YUY2	(1) 1920 x 1080	(2) 1280 x 720	(3) 640 x 360
Output Format	H.264; YUY2; MJPG		
Field of View	FOV 120° (D)		
Adjustable Angle	±15° (V)		
Focus Mode	Fixed-Focus		
Focus Distance	1m		
Special Features	① Auto Framing: automatic FOV adjustment to fit in all participants; ② Speaker Tracking: voice triggered people tracking; ③ 3 zoom presets to instantly set up the conference		

Audio**Speaker**

Sound Channel	1.1
Output Power	8 W + 3 W
Maximum Sound Pressure	83 dB SPL@1 m
Signal to Noise Ratio	>75 dB
Frequency Range	150 Hz ~ 18 kHz

Microphone

Quantity	6
Voice Pickup Range	100 Hz~7.5 kHz
Microphone Frequency Range	100 Hz ~ 7.5 kHz
Special Features	Noise Reduction, Echo Cancellation, Anti-Reverberation, Built-in AGC Algorithm

PIR Sensor

In power-on mode, the device automatically enters standby mode If no moving object is detected within 3 meters for 30 minutes, minimizing energy consumption.

In standby mode, the device automatically starts up on detecting moving objects within 3 meters, simplifying the setup process.

Input/Output Port

USB 3.0 Type-C	Connect USB host, upgrade system, etc.
USB 3.0 Type-A	Flash drive, keyboard, mouse, etc.
USB 2.0 Type-A	Flash drive, keyboard, mouse
AUDIO OUT	Used for external audio equipment
HDMI OUT	HDMI 2.0, supports 280*720p, 1920*1080p, 3840*2160p, supports CEC
DC 2.0	Used for 12 V power input power supply
RJ45	IP support, PoE power support

Power

Power Requirements	12 V
Standby mode power consumption	≤ 0.5 W
PoE Power	Yes (IEEE 802.3af or 802.3at)

Operating System

System Version	Android 9.0
RAM	4 G
ROM	16 G
CPU	2×A72+4×A53

Wi-Fi

Wi-Fi Protocol	802.11ac/n/g/b/a/ax
Working Band	2.4 GHz; 5 GHz
Working Mode	AP+STA
Working Distance	0~10 m

Bluetooth

Version	5.0
Protocol	A2DP;HFP;HSP;AVRCP;BLE
Working Distance	0~10 m

Mount

- Wall-mount
- TV mount kit (Optional)

Physical Specifications

Dimension L×H×W	462×76×93 mm (18.2x3.0x3.7 inch)
Dimension (package) L×W×H	1 pc: 538x160x169 mm (21.2x6.3x6.7 inch) 4pcs: 628x433x380 mm (24.7x17.0x15.0 inch)
Net Weight	1.20 kg (2.65 lb)
Gross Weight	1 pc: 2.74 kg (6.04 lb) 4 pcs: 12.90 kg (28.44 lb)

Environmental Conditions

Operation Temperature	0 °C~40 °C
Operation Humidity	10%~90%RH
Storage Temperature	-20 °C~60 °C
Storage Humidity	10%~90%RH
Below 5000 meters	

Application Supported

- MAXHUB Meeting OS
- MAXHUB Share
- MAXHUB Pivot
- MAXHUB Share
- Whiteboard

Compatibility

Supports major VC software including ZOOM, Microsoft® Teams, Google Meet, Google Hangouts, Cisco WebEx®, RingCentral, etc.

Warranty

- 3 Years hot-swap
- Accessories 1 year

Compatible BYOM Dongle

MAXHUB WT13M

What's in the box

- HDMI Cable 1.5 m (59.1 inch)
- USB 3.0 Cable 1.8 m (70.87 inch)
- USB 2.0 Cable 3 m (118.11 inch)
- Lens Cover
- Wall-mounted Components
- Power Adapter
- Remote Control
- User Manual



MAXHUB
Beyond Collaboration